



Items list for priming:

- ✓ Clean, lint free cloth or compressed air
- ✓ Good quality exterior primer
(latex primer on wood shutters – oil-based primer on RockBridge Composite shutters)



Shutters By Design highly recommends ordering your shutters factory primed and/or painted here in our shop. Our Limited Lifetime Warranty fully applies only when all work is completed by Shutters By Design professionals. If you do choose to prime your shutters, the below tips are guidelines only. Shutters By Design suggests contacting your trusted local paint supply store and ask for high quality exterior primer recommend for your area.

PRIMING TIPS

These priming tips are guidelines only.

Prior to priming:

- Use a clean and lint free cloth or compressed air to remove any dust from shutters;
- Apply one coat of high-quality exterior primer - following the priming manufacturer's instructions completely; and
- Let primer dry per the manufacturer's instructions.

Caution:

Do not allow shutters to stay or to be stored in direct sunlight.

Do not let shutters dry in direct sunlight after priming.

Do not lean shutters against one another, they will stick together, even if the primer feels dry.

PLEASE FOLLOW PRIMER MANUFACTURERS INSTRUCTIONS AT ALL TIMES.

Shutters By Design is not responsible for damages as a result of following the above priming tips.

Shutters By Design will not be held liable for any damage or defects resulting from modification or repairs done by the customer. Shutters By Design will not pay for any priming, painting or re-installation of our shutters due to modifications, repairs or replacement. Paint or primer not applied by Shutters By Design voids our Limited Lifetime Warranty and the manufacturer's warranty of the paint or primer is the only valid warranty. Claims must be made to the warranty department of the paint or primer manufacturer.